

Weld Bodies VeriFast™ IA Quick Reference

No.	VeriFast™ IA Weld Body Style	Insulated Body	Series					Stroke (mm)				Cable Exit Position				Weld Pin Style	Weld Body Foot Print / Other Details
			2	3	4	22	50	Top Left	Top Right	Top Middle	Pre-Defined						
1	 SXAR (Base Mount)	X	✓	✓	✓	✓	X	✓	✓	X	X	✓	✓	X	X	 DB Style Weld Pin Assembly	 3.00" (76.20 mm) 2.38" (60.45 mm) 1.00" (25.40 mm) 1.50" (38.10 mm)
2	 SXKR (Base Mount)	✓	✓	✓	✓	✓	X	X	X	✓	X	✓	✓	X	X	 DB Style Weld Pin Assembly	
3	 SXTR (Base Mount)	X	✓	✓	✓	✓	X	X	X	✓	X	✓	✓	X	X	 DB Style Weld Pin Assembly	 2.75" (69.85 mm) (for Series 2) 2.94" (74.68 mm) (for Series 3) 3.06" (77.72 mm) (for Series 4) 1.00" (25.40 mm) 1.00" (25.40 mm) 1.74" (44.20 mm)
4	 SXQR (Base Mount)	✓	✓	✓	✓	✓	X	X	X	✓	X	✓	✓	X	X	 DB Style Weld Pin Assembly	 1.00" (25.40 mm) 1.00" (25.40 mm) 1.74" (44.20 mm) 2.00" (50.80 mm) 2.25" (57.15 mm)
5	 SXHR (Base Mount)	✓	✓	✓	✓	✓	X	✓	✓	X	X	✓	✓	X	X	 DB Style Weld Pin Assembly	 1.50" (38.10 mm) 0.31" (7.94 mm) 0.25" (6.35 mm) 0.75" (19.05 mm)
6	 SXJR (Base Mount)	✓	✓	✓	✓	✓	X	✓	✓	X	X	✓	✓	X	X	 DB Style Weld Pin Assembly	 1.50" (38.10 mm) 1.00" (25.40 mm) 2.38" (60.33 mm) 4.00" (101.60 mm) 4.75" (120.65 mm)
7	 SXVR (Base Mount)	X	✓	X	X	✓	X	X	X	✓	X	✓	✓	X	X	 DB Style Weld Pin Assembly	 2.75" (69.85 mm) 1.15" (29.21 mm) 1.00" (25.40 mm) 1.00" (25.40 mm) 1.75" (44.45 mm)
8	 SXWR (Base Mount)	✓	✓	X	X	✓	X	X	X	✓	X	✓	✓	X	X	 DB Style Weld Pin Assembly	 1.00" (25.40 mm) 2.00" (50.80 mm) 2.25" (57.15 mm)

✓=Recommended X=Not Available ✓=Available, Not Recommended

Weld Bodies VeriFast™ IA Quick Reference

No.	VeriFast™ IA Weld Body Style	Insulated Body	Series					Stroke (mm)				Cable Exit Position				Weld Pin Style	Weld Body Foot Print / Other Details
			2	3	4	22	50	Top Left	Top Right	Top Middle	Pre-Defined						
9	 SXCR (Tapered)	X	X	✓	X	✓	X	X	X	X	X	✓	✓	X	✓	 DB Style Weld Pin Assembly	 1.38" (35.05 mm) 1.80" (20.24 mm)
10	 SXFR (Threaded)	X	X	✓	X	✓	X	X	X	X	X	✓	✓	X	✓	 DB Style Weld Pin Assembly	 1.38" (35.05 mm) 1.80" (20.24 mm)
11	 SXGR (Threaded)	X	X	✓	X	✓	X	X	X	X	X	✓	✓	X	✓	 DB Style Weld Pin Assembly	 1.38" (35.05 mm) 1.80" (20.24 mm)
12	 Clamp Mount	X	✓	✓	✓	✓	✓	✓	X	X	X	✓	✓	X	✓	 Tapped Custom Weld Pin (Contact CenterLine for design)	 22 mm Pin Stroke 31.75 mm 100 mm 124 mm (for Series 2) 124 mm (for Series 3) 127 mm (for Series 4) 22 mm Pin Stroke 31.75 mm 140 mm 124 mm (for Series 2) 124 mm (for Series 3) 127 mm (for Series 4) 50 mm Pin Stroke 31.75 mm 140 mm 137 mm (for Series 2) 138 mm (for Series 3) 143 mm (for Series 4)
13	 SYVR (Base Mount)	X	✓	✓	✓	X	✓	X	X	✓	X	✓	✓	X	X	 HE Style Weld Pin Assembly	 0.37" (9.40 mm) 1.74" (44.20 mm) 3.97" (100.84 mm) (for Series 2) 4.28" (108.71 mm) (for Series 3 and 4) 0.50" (12.70 mm) (for Series 2) 0.81" (20.57 mm) (for Series 3 and 4) 1.75" (44.45 mm) (for Series 2) 2.06" (52.32 mm) (for Series 3 and 4) 1.5" (38.10 mm) 1.00" (25.40 mm)

✓ = Recommended X = Not Available ✓ = Available, Not Recommended